



## QuickSeam™ Splice Tape

### Firestone Item Number:

- W56RAC1603: 76.3 mm x 30.48 m (3.0" x 100.0') rolls
- W56RAC1617: 177.8 mm x 30.48 m (7.0" x 100.0') rolls
- W56RAC1698: 76.3 mm x 7.63 m (3.0" x 25.0') rolls
- W56RAC1626: 152.4 mm x 30.48 m (6.0" x 100.0') rolls

### DESCRIPTION:

Firestone QuickSeam Splice Tape is designed for field splicing of approved Firestone membrane panels.

### METHOD OF APPLICATION:

Use QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus™ pad and handle to clean and prime mating surfaces. Install QuickSeam Splice Tape in accordance with Firestone Specialty Products specifications and details.

### SHELF LIFE:

1. Shelf life of one (1) years can be expected if stored in original unopened container at temperatures between 15.6 - 26.7° C (60 - 80° F).
2. Shelf life will be shortened if exposed to elevated temperatures.
3. Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

### STORAGE:

1. Store in original unopened containers at temperatures between 15.6 - 26.7° C (60 - 80° F) until ready for use.
2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for application.



### PRODUCT DATA

Property	Minimum Performance
Base:	Rubber Polymers
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	0.77 mm +/- 0.127 mm (0.030" +/- 0.005")
Width:	76.3 mm (3.0") 152.4 mm (6.0") 177.8 mm (7.0")

### Physical Characteristics:

1. Excellent moisture resistance.
2. Excellent resistance to heat and cold
3. Excellent green tack.

### PACKAGING:

SI		Eng		Rolls/ Carton	Cartons/ Pallet
Width	Length	Width	Length		
76.3 mm	30.48 m	3.0"	100.0'	6	40
177.8 mm	30.48 m	7.0"	100.0'	2	56
76.3 mm	7.63 m	3.0"	25.0'	16	80
152.4 mm	30.48 m	6.0"	100.0'	2	56

QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

### PRECAUTIONARY DATA:

Review Material Safety Data Sheet (MSDS) prior to use.

### LEED INFORMATION:

Post Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Prescott, AR

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.