



QuickSeam™ Tape Kit


Firestone Item Number:
W56RAC1690: QuickSeam Tape Kit
DESCRIPTION:

This consumer grade seaming kit contains all the items necessary to complete 7.01 m (25.0') of seams for approved Firestone membranes. Included with the kit are step by step instructions on how to complete the seaming process.

SHELF LIFE:

1. Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 15.6 - 26.7° C (60 - 80° F).
2. Shelf life will be shortened if exposed to elevated temperatures.
3. Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

STORAGE:

1. Store in original unopened containers at temperatures between 15.6 - 26.7° C (60 - 80° F) until ready for use.
2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for application.

PACKAGING:

The carton contains all items listed in the Product Data section.

PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
QuickSeam Tape:	7.01 m of 76.2 mm (25.0' of 3.0") QuickSeam Tape (See QuickSeam Tape for more info)
* TPO QuickPrime™	2 x 113.4 g (4 oz) cans
QuickScrubber™ Handle:	1 Each
QuickScrubber Pad:	2 Each
Wipes:	4 Each- 304.8 x 304.8 mm (12.0" x 12.0")
Seam Roller:	1 Each
Special Crayon:	1 Each
Instructions:	1 Each

PRECAUTIONARY DATA:

1. Review Material Safety Data Sheet (MSDS) prior to use.
2. Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
3. Red caution labels are required when shipping.
4. Use only in well ventilated areas.
5. Avoid contact with skin. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
6. Use only in conjunction with QuickScrubber or QuickScrubber Plus™ pad and handle. Do not apply with rollers, brushes or rags.
7. Mix thoroughly before and during use.
8. Thinning is not allowed.
9. Keep out of reach of children.
10. Dispose as a hazardous waste in accordance with local, state and federal regulations.
11. Recommended cleaner is rubbing alcohol followed by soap and water.
12. Do not contaminate with foreign materials.
13. Cover can when not in use. When applying adhesive, work out of small pails with a cover to avoid skimming over of adhesive in larger can.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone Specialty Products
250 West 96th Street, Indianapolis, Indiana 46260
Specialty Products (800) 428-4442
Internet Address: <http://www.firestonesp.com>