TECHNICAL INFORMATION SHEET



Silicone Rubber Roller

Firestone Item Number:

W563582023: 38.1 mm (1.5") Silicone

Rubber Roller

DESCRIPTION:

Silicone Rubber Roller consists of a 38.1 mm (1.5") silicone rubber covered steel roller with a wooden handle. The roller is designed to be used to mate approved Firestone membranes with Firestone's QuickSeam Cover Strip or QuickSeam Seam Tape and for rolling QuickSeam Flashing that has been applied for sealing details.

PACKAGING:

38.1 mm (1.5") roller is packaged six per carton and 42 cartons per pallet.

PRECAUTIONARY DATA:

- Keep roller clean and free from adhesive or other contaminant buildup.
- Roller may be cleaned with SP-100 Splice Wash or other compatible solvent.



PRODUCT DATA

<u>Property</u> <u>Minimum Performance</u>

Welded Roller Shaft:

Handle: 101.6 mm (4.0") Long, 25.4mm (1.0")

Dia., Wooden Handle

Roller: 38.1 mm (1.5") Dia., Steel with Bronze

Sleeve Bearings with a Silicone sleeve 19 mm (0.75") Dia., 50.8 mm (2.0")

Long, Steel

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

250 West 96th Street, Indianapolis, Indiana 46260 Specialty Products (800) 428-4442 Internet Address: http://www.firestonesp.com