

**LAP SEALANT HS**

**1. Identification of the substance/preparation and of the company/undertaking**

**1.1 Identification of the substance or preparation:**

Synonyms: none  
 CAS No. : N.A.  
 EC index No. : N.A. NFPA code : 2-3-0\*  
 EINECS No. : N.A. Molecular weight : N.A.  
 RTECS No. : N.A. Formula : N.A.

**1.2 Use of the substance or the preparation:**

Sealant  
 Adhesive

**1.3 Company/undertaking identification:**

Firestone Building Products  
 Ikaroslaan 75  
 B-1930 Zaventem  
 Tel. : +32 2 711 44 50  
 Fax : +32 2 721 27 18  
 Email: info@fbpe.be

**1.4 Telephone number for emergency:**

+32 70 245 245  
 Poison Centre  
 p/a Militair Hospitaal Koningin Astrid, Bruynstraat, B-1120 Brussel

**2. Composition/information on ingredients**

Hazardous ingredients	CAS No. EINECS/ELINCS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
kerosine, unspecified	64742-47-8 265-149-8	15-20	Xn;N	10-38-51/53-65-67 (Labelling in compliance with CONCAWE )(1)
quartz (SiO <sub>2</sub> )	14808-60-7 238-878-4	<1	T	49 (1)

(1) For R-phrases in full: see heading 16

**3. Hazards identification**

- Highly flammable
- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- Repeated exposure may cause skin dryness or cracking
- Vapours may cause drowsiness and dizziness

**4. First aid measures**

**4.1 Eye contact:**

- Consult a doctor/medical service if irritation persists
- Rinse immediately with water

**4.2 Skin contact:**

- Consult a doctor/medical service if irritation persists
- Clean with alcohol
- Wash with water and soap

## LAP SEALANT HS

### 4.3 After inhalation:

- Consult a doctor/medical service if breathing problems develop
- Remove the victim into fresh air

### 4.4 After ingestion:

- Consult a doctor/medical service if you feel unwell
- Immediately give lots of water to drink
- Never give water to an unconscious person
- Do not induce vomiting

## 5. Fire-fighting measures

### 5.1 Suitable extinguishing media:

- Water spray
- Polyvalent foam
- BC powder
- Carbon dioxide

### 5.2 Unsuitable extinguishing media:

- Container may slop over if solid jet is applied

### 5.3 Special exposure hazards:

- Gas/vapour spreads at floor level: ignition hazard
- Gas/vapour flammable with air within explosion limits
- Upon combustion CO and CO<sub>2</sub> are formed

### 5.4 Instructions:

- If exposed to fire cool the closed containers by spraying with water
- Take account of environmentally hazardous firefighting water
- Use firefighting water moderately and contain it

### 5.5 Special protective equipment for firefighters:

- Protective clothing for exposure to chemicals

## 6. Accidental release measures

### 6.1 Personal protection/precautions:

See heading 8.2/8.3/13

### 6.2 Environmental precautions:

- Prevent soil and water pollution
- Prevent spreading in sewers
- Contain leaking substance
- Dam up the solid spill
- Try to reduce evaporation

### 6.3 Methods for cleaning up:

- Scoop solid spill into closing containers
- Carefully collect the spill/leftovers
- Clean contaminated surfaces with an excess of water
- Wash clothing and equipment after handling

## 7. Handling and storage

### 7.1 Handling:

- Insufficient ventilation:
- Avoid prolonged and repeated contact with skin
- Use spark-/explosionproof appliances and lighting system
- Take precautions against electrostatic charges
- Do not discharge the waste into the drain

### 7.2 Storage:

- Keep container tightly closed
- Store at room temperature
- Keep out of direct sunlight
- Store in a dry area
- Keep away from: heat sources, ignition sources, acids, bases

# LAP SEALANT HS

Storage temperature : 15/25 °C  
Quantity limits : N.D. kg  
Storage life : 365 days  
Materials for packaging :  
- suitable : no data available  
- to avoid : no data available

## 7.3 Specific uses:

- See information supplied by the manufacturer

## 8. Exposure controls/Personal protection

### 8.1 Exposure limit values:

quartz (SiO<sub>2</sub>)

TLV-TWA	: (0.05 R)	mg/m <sup>3</sup>		ppm
TLV-STEL	: -	mg/m <sup>3</sup>		ppm
MEL-LTEL	: 0.3 R	mg/m <sup>3</sup>	-	ppm
MEL-STEL	:	mg/m <sup>3</sup>		ppm
MAK	: -	mg/m <sup>3</sup>	-	ppm
MAC-TGG 8 h	: 0.075 R	mg/m <sup>3</sup>		
MAC-TGG 15 min.	:	mg/m <sup>3</sup>		
VME-8 h	: 0.1 A	mg/m <sup>3</sup>	-	ppm
VLE-15 min.	: -	mg/m <sup>3</sup>	-	ppm
GWBB-8 h	: 0.1 R	mg/m <sup>3</sup>	-	ppm
GWK-15 min.	: -	mg/m <sup>3</sup>	-	ppm
Momentary value	:	mg/m <sup>3</sup>		ppm
EC	:	mg/m <sup>3</sup>		ppm
EC-STEL	:	mg/m <sup>3</sup>		ppm

### Sampling methods:

- Silica, Crystalline, Respirable	NIOSH 7500
- Silica (Quartz, Non-Respirable) (See Dust, Total nuisance)	OSHA CSI
- Silica, Crystalline	NIOSH 7602
- Silica, Crystalline Quartz, Respirable Dust	OSHA ID 142
- Kerosene (Naphthas)	NIOSH 1550
- Kerosene	OSHA CSI
- Silica, Crystalline	NIOSH 7601

### 8.2 Exposure controls:

#### 8.2.1 Occupational exposure controls:

- Measure the concentration in the air regularly  
- Work under local exhaust/ventilation

#### 8.2.2 Environmental exposure controls: see heading 13

### 8.3 Personal protection:

#### 8.3.1 respiratory protection:

- Gas mask with filter type A  
- Insufficient ventilation: wear respiratory protection

#### 8.3.2 hand protection:

- Gloves  
Suitable materials: Nitrile rubber  
PVA  
- Breakthrough time: N.D.

#### 8.3.3 eye protection:

- Protective goggles

## LAP SEALANT HS

### 8.3.4 skin protection:

- Protective clothing
- Suitable materials:

Nitrile rubber  
PVA

## 9. Physical and chemical properties

### 9.1 General information:

Appearance (at 20°C) : Paste  
Odour : Characteristic  
Colour : Black

### 9.2 Important health, safety and environmental information:

pH value : N.D.  
Boiling point/boiling range : 116 °C  
Flashpoint : 11 °C  
Explosion limits : 0.9/6.7 vol% ( °C)  
Vapour pressure (at 26°C) : 60 hPa  
Vapour pressure (at 50°C) : N.D. hPa  
Relative density (at 20°C) : 1.1/1.4  
Water solubility : < 0.5 g/100 ml  
Soluble in : N.D.  
Relative vapour density : 3.8  
Viscosity : N.D. Pa.s  
Partition coefficient n-octanol/water : N.D.  
Evaporation rate : N.D.  
ratio to butyl acetate : N.D.  
ratio to ether : N.D.

### 9.3 Other information:

Melting point/melting range : N.D. °C  
Auto-ignition point : N.D. °C  
Saturation concentration : N.D. g/m<sup>3</sup>

## 10. Stability and reactivity

### 10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

### 10.2 Materials to avoid:

- Keep away from: heat sources, ignition sources, acids, bases

### 10.3 Hazardous decomposition products:

- Upon combustion CO and CO<sub>2</sub> are formed

## 11. Toxicological information

### 11.1 Acute toxicity:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

### 11.2 Chronic toxicity:

quartz (SiO<sub>2</sub>)

EC carc. cat.	: 1
EC muta. cat.	: not listed
EC repr. cat.	: not listed

Carcinogenicity (TLV)	: A2
Carcinogenicity (MAC)	: K
Carcinogenicity (VME)	: not listed
Carcinogenicity (GWBB)	: not listed

Carcinogenicity (MAK)	: 1
Mutagenicity (MAK)	: not listed
Teratogenicity (MAK)	: -

IARC classification	: 1
---------------------	-----

11.3 Routes of exposure: ingestion, inhalation, eyes and skin

### 11.4 Acute effects/symptoms:

- **AFTER INHALATION**
- EXPOSURE TO HIGH CONCENTRATIONS:
- CNS depression
- Dizziness
- Headache
- Nausea
- Narcosis
- Disturbances of consciousness
- **AFTER SKIN CONTACT**
- ON CONTINUOUS EXPOSURE/CONTACT:
- Dry skin
- Cracking of the skin
- **AFTER EYE CONTACT**
- Slight irritation

### 11.5 Chronic effects:

- Not listed in carcinogenicity class (IARC,EC,TLV,MAK)
- Not listed in mutagenicity class (EC,MAK)
- Not classified as toxic to reproduction (EC)

# LAP SEALANT HS

## 12. Ecological information

### 12.1 Ecotoxicity:

- No data available

### 12.2 Mobility:

- Volatile organic compounds (VOC): N.D.%
- Insoluble in water
- Substance sinks in water

For other physicochemical properties see heading 9

### 12.3 Persistence and degradability:

- biodegradation BOD<sub>5</sub> : N.D. % ThOD
- water : - No data available
- soil : T ½: N.D. days

### 12.4 Bioaccumulative potential:

- log P<sub>ow</sub> : N.D.
- BCF : N.D.

### 12.5 Other adverse effects:

- WGK : 2 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : no data available
- Effect on waste water purification : no data available

## 13. Disposal considerations

### 13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 04 09\* (waste adhesives and sealants containing organic solvents or other dangerous substances)
- Hazardous waste (91/689/EEC)


### 13.2 Disposal methods:

- Remove to an authorized plant for the destruction, neutralization and elimination of hazardous waste
- Use appropriate containment to avoid environmental contamination

### 13.3 Packaging/Container:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10\* (packaging containing residues of or contaminated by dangerous substances)

## 14. Transport information



- 14.1 Classification of the substance in compliance with UN Recommendations**
- UN number : 1133  
 CLASS : 3  
 SUB RISKS : -  
 PACKING : III  
 PROPER SHIPPING NAME :  
 UN 1133, Adhesives, Special provision 640H
- 14.2 ADR (transport by road)**
- CLASS : 3  
 PACKING : III  
 CLASSIFICATION CODE : F1  
 DANGER LABEL TANKS : 3  
 DANGER LABEL PACKAGES : 3
- 14.3 RID (transport by rail)**
- CLASS : 3  
 PACKING : III  
 CLASSIFICATION CODE : F1  
 DANGER LABEL TANKS : 3  
 DANGER LABEL PACKAGES : 3
- 14.4 ADNR (transport by inland waterways)**
- CLASS : 3  
 PACKING : III  
 CLASSIFICATION CODE : F1  
 DANGER LABEL TANKS : 3  
 DANGER LABEL PACKAGES : 3
- 14.5 IMDG (maritime transport)**
- CLASS : 3  
 SUB RISKS : -  
 PACKING : III  
 MFAG : -  
 EMS : F-E, S-D  
 MARINE POLLUTANT : -
- 14.6 ICAO (air transport)**
- CLASS : 3  
 SUB RISKS : -  
 PACKING : III  
 PACKING INSTRUCTIONS PASSENGER AIRCRAFT : 309/Y309  
 PACKING INSTRUCTIONS CARGO AIRCRAFT : 310
- 14.7 Special precautions in connection with transport** : Transport in tanks: not applicable Viscous liquid with a flash point lower than 23 C,
- 14.8 Limited quantities (LQ)** :

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4, **only** the following prescriptions shall be complied with:  
 each package shall display a diamond-shaped figure with the following inscription:  
 - 'UN 1133'  
 or, in the case of different goods with different identification numbers within a single package:  
 - the letters 'LQ'

# LAP SEALANT HS

## 15. Regulatory information

Classification according to directives 67/548/EEC and 1999/45/EC



Highly flammable

R11	:	Highly flammable
R52/53	:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R66	:	Repeated exposure may cause skin dryness or cracking
R67	:	Vapours may cause drowsiness and dizziness
S(02)	:	(Keep out of reach of children)
S16	:	Keep away from sources of ignition - No smoking
S(46)	:	(If swallowed, seek medical advice immediately and show this container or label)
S61	:	Avoid release to the environment. Refer to special instructions/safety data sheets.



## 16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**N.A.** = NOT APPLICABLE  
**N.D.** = NOT DETERMINED  
**(\*)** = INTERNAL CLASSIFICATION (NFPA)

### Exposure limits:

**TLV** : Threshold Limit Value - ACGIH USA  
**OES** : Occupational Exposure Standards - United Kingdom  
**MEL** : Maximum Exposure Limits - United Kingdom  
**MAK** : Maximale Arbeitsplatzkonzentrationen - Germany  
**TRK** : Technische Richtkonzentrationen - Germany  
**MAC** : Maximale aanvaarde concentratie - The Netherlands  
**VME** : Valeurs limites de Moyenne d'Exposition - France  
**VLE** : Valeurs limites d'Exposition à court terme - France  
**GWBB** : Grenswaarde beroepsmatige blootstelling - Belgium  
**GWK** : Grenswaarde kortstondige blootstelling - Belgium  
**EC** : Indicative occupational exposure limit values - directive 2000/39/EC

**I** : Inhalable fraction = **T**: Total dust = **E**: Einatembarer Aerosolanteil  
**R** : Respirable fraction = **A**: Alveolengängiger Aerosolanteil/Alveolar dust  
**C** : Ceiling limit

<b>a:</b>	aerosol	<b>r:</b>	rook/Rauch	(fume)
<b>d:</b>	damp (vapour)	<b>st:</b>	stof/Staub	(dust)
<b>du:</b>	dust	<b>ve:</b>	vezel	(fibre)
<b>fa:</b>	Faser (fibre)	<b>va:</b>	vapour	
<b>fi:</b>	fibre	<b>om:</b>	oil mist	
<b>fu:</b>	fume	<b>on:</b>	olienevel/Ölnebel	(oil mist)
<b>p:</b>	poussière (dust)	<b>part:</b>	particles	

### Chronic toxicity:

**K** : List of the carcinogenic substances and processes - The Netherlands

### Full text of any R-phrases referred to under heading 2:

R10 : Flammable  
R38 : Irritating to skin  
R49 : May cause cancer by inhalation  
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment  
R65 : Harmful: may cause lung damage if swallowed  
R66 : Repeated exposure may cause skin dryness or cracking  
R67 : Vapours may cause drowsiness and dizziness